

AIMR-0404

IP-MPLS Access Router

Feature Summary

- ◆ Compact 1RU , 19" standard rack mountable
- ◆ Hot-swappable AC/DC power supplies with 1+1 redundancy
- ◆ Supports variety of physical interfaces such as 1GE, 10GE and E1 interfaces**
- ◆ Hot swappable fan module with redundant fans
- ◆ Supports sub-50ms protection by means of 1:1 LSP/PW, LAG, SNCP, ERPS, dual-homing, VRRP
- ◆ Support 100 Gbps full-duplex switching capacity
- ◆ Supports NTP, SyncE and IEEE 1588v2 clock synchronization
- ◆ Supports MPLS Processing Capabilities using standard IP MPLS and SR MPLS Technology
- ◆ Supports powerful routing and IP Multicasting capabilities
- ◆ Support IPv4 /IPv6 static and dynamic routing
- ◆ Supports full carrier-ethernet functionalities including BFD and Ethernet OAM
- ◆ Compliant with TEC-GR 48050-2024.

Layer 2 and Layer 3 features

- ◆ Supports Carrier-ethernet functionalities such as L2/L3 VPN, EPL, EVPL, VLL, E-LAN and VPLS, E-LINE, E-TREE, CES emulation, L2 MAC address Learning, Jumbo Frames, VLAN per IEEE 802.1Q and IEEE 802.1ad, Port Mirroring, DHCP, STP, RSTP, MSTP, ERPS/ ITU T G.8032 v2, Open ERPS, LLDP, LLC, Flow Control, Link Aggregation & LACP, Egress Buffering, PWE3, Ethernet OAM and QOS
- ◆ MPLS (MPLS-TE/RSVP), LDP, MPLS Class of service, Segmented routing (SR-TE) and PCEP, R-LFA, Ti-LFA and BFD
- ◆ Static routing (IPv4 and IPv6) and L3 Protocols such as OSPF, OSPFv2, OSPFv3, eBGP, IBGP, ISIS, ECMP
- ◆ Provides network reliability by IP FRR, TE FRR, PW Redundancy, VPN FRR,VRRP
- ◆ IP multicast services based on IGMP v2/3, PIM SM/SSM

Security

- ◆ RADIUS, GTSM, DoS attack prevention, MAC address limitation and aging, MAC address spoofing prevention, Traffic Filtering, TACACS+, CAC

The Alphion AIMR-0404 is a high capacity, high density rack mount Metro Access Aggregation device switch for 3G/4G/5G mobile xHaul and broadband network.

Applications

The Alphion AIMR-0404 provide stable, reliable, secure high performance L2/L3 switching services in order to meet the requirements of an access network. It adopts MPLS technology and comply with the latest MPLS standards defined by IETF, MEF 3/6/8, ITU-T and other international standards.

Standards

Alphion AIMR-0404 is compliant with the following standards:

IEEE Protocols:

802.1p, 802.1Q, 802.1ad, 802.3ad, 802.3ah, 802.1ag, 802.3x, 802.3z, 802.3ab, 802.3ac, 802.3ae, 1588v2.

IETF RFCs:

1112,1850,2236,2370,2439,2457,2474,2475, 2544, 2547, 2554, 2597, 2598, 2740, 3101, 3107, 3140, 3246,4364,4448,4618,4761,4762,4842, 6020,6241,7011,7012.

ITU-T Specifications:

Y.1731, G.8113.1, G.8113.2, Y.1564.

Management

Alphion AIMR-0404 provides ease of management via SNMP, NetConf/YANG. It also supports Zero-touch provisioning.

SPECIFICATIONS

Ethernet I/O Interfaces

1GE/10GE: 8 x SFP/SFP+ ports
E1: 16 ports**

Transceivers Supported

SFP+: 10GBASE -SR, 10GBASE-LR, 10GBASE-ER and 10GBASE-ZR
SFP: 1000BASE-SX, 1000BASE-LX, 1000BASE-EX and 1000BASE-ZX

Timing Interfaces

CLK1/2

Management Interfaces

Out-of-band, Console

Performance

Switching: 100 Gbps Ethernet switching
Capacity

Scalability

No. of Routes IPv4 – 10K, IPv6 – 2k
Virtual Routing Functions (VRF) 32
Routes-Per-VRF 5K
No. of. Route Entries (OSPF) 1K
Forwarding DB (MAC) 32K

Power

AC Option: Hot swappable Dual-AC, 1+1 redundant PSU
AC Input: 100 ~ 240V, 50-60Hz
DC Option: Dual-DC, 1+1 redundant Inputs
DC Input: -48V +/-20%
Consumption: 90 W (Max.)

Physical

Operating Temp: -5°C to 55°C
Operating (RH): 5% to 95% (RH), Non-condensing
Dimensions: 442 mm (W) X 235 mm (D) X 44.45 mm (H)
Weight: 4.5 Kg (approx.)
Cooling: Hot swappable fan tray with 3+1 redundant fans

Regulatory Compliance

EMC: ETSI EN 300 386, EN 55022, EN55024, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, CISPR 22, CISPR 24,
Safety: IEC/EN 60825-1, IEC/EN 60950-1, IEC/EN 62368-1

** Contact Alphion Sales

The information contained herein is for informational purposes only. Technical claims listed depend on various technical assumptions. Your experience with these products may differ if you operate the products in an environment which is different from the technical assumptions. Alphion reserves the right to modify these specifications without any prior notice. Alphion makes no warranties, expressed or implied, on the contained in this document.